



# STAR SMALL EINBAUSTRALER | SPOT INCASSO

LED LIGHTING



**SERIE B535-R**  
**BEWEGLICH - ORIENTABILE**  
**OHNE DRIVER - SENZA DRIVER**

**44 MM AUSSCHNITT - FORO 44 MM**



## EIGENSCHAFTEN | CARATTERISTICHE

| Farbe<br>Colore | Art. Nr.     | W   | CREE<br>COB   | LM     | K      | CRI<br>RA | Optik |       |
|-----------------|--------------|-----|---------------|--------|--------|-----------|-------|-------|
| ○               | B535-R303003 | 4 W | 350 mA / 13 V | 350 lm | 3000 K | > 90      | 30°   | 44 mm |
| ●               | B535-R303005 | 4 W | 350 mA / 13 V | 350 lm | 3000 K | > 90      | 30°   | 44 mm |

## PASSENDES NETZTEIL | ALIMENTATORE ADATTO



| Art. Nr.      | W   | V in        | Amp. | V out     | Amp. out | IP | ta | Dimensions   | VP  |
|---------------|-----|-------------|------|-----------|----------|----|----|--------------|-----|
| B96-G6RT350CC | 9 W | 220 - 240 V | /    | 13 - 26 V | 350 mA   | /  | /  | Ø 48 x 25 mm | 100 |

Dali > siehe Netzteile | Dali > vedi alimentatori Siehe Seite 241-247 | Vedi pagina 241-247

## LICHTVERTEILUNG | DISTRIBUZIONE DELLA LUCE

